(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 15 July 2004 (15.07.2004)

PCT

(10) International Publication Number WO 2004/059360 A1

(51) International Patent Classification7: C08K 5/053

G02B 6/44.

(21) International Application Number:

PCT/EP2002/014773

(22) International Filing Date:

27 December 2002 (27.12.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): PIRELLI & C. S.P.A. [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT).

(72) Inventors: and

(75) Inventors/Applicants (for US only): DONETTI, Raffaella [IT/IT]; Via 10 Martini, 16, I-28074 Ghemme (IT). PAVAN, Massimiliano [IT/IT]; Via degli Alpini, 9, I-24049 Verdello (IF). BRANDI, Giovanni [IT/IT]; Piazza Aspromonte, 24, I-20131 Milano (IT). MARITANO, Mauro [IT/IT]; Via Molise, 15, I-20052 Monza (IT).

(74) Agents: MANCINI, Vincenzo et al.; Ing. A. Giambrocono & C. Srl, Via Rosolino Pilo, 19/B, I-20129 Milan (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WATER-RESISTANT TELECOMMUNICATION CABLE



drolysis degree of about 60 % to about 95 % and a polymerisation degree higher than about 2,500; at least a first solid plasticizer, having a melting point between 50° and 110°C, and a second solid plasticizer, having a melting point equal or higher than 140°C, in an amount of about 10-30 and 1-10 parts by weight per hundred parts by weight of the copolymer, respectively; the water-soluble polymer material showing: a complex modulus (G*) equal or higher than 2.5 106 Mpa; a ratio of the viscous modulus to the elastic modulus (tanσ)equal or lower than 2.30; a glass transition temperature (Tg) of about 20° to about 35°C.